

# Power Drain Cleaner Comparison Chart

	Typical Applications	For Use in Following Pipe Sizes	Maximum Capacity	Operating Weight	Maximum Recommended Distance	Motor Horsepower
<b>Super-Vee Power-Vee Handylelectric</b> Pages 4 – 7	Sinks, Bathtubs, Roofstacks	1-1/4" – 3" 30 mm x 75 mm	35 ft. x 3/8" or 50 ft. x 1/4" or 5/16" 10.5 m x 9.5 mm or 15 m x 7.9 mm	16 lbs. with 25 ft. x 3/8" 7 kg	50 ft. 15 m	3.2 amp
<b>Drain-Rooter</b> Page 8				29 lbs./13 kg		
<b>Drain-Rooter PH</b> Page 9				34 lbs./15 kg		
<b>Mini-Rooter Mini-Rooter XP</b> Pages 10 – 13	Small Drains, Inside Work, On Roofs	1-1/4" – 3" and most 4" 30 mm – 100 mm (Not For Roots)	75 ft. x 1/2" or 3/8" 22.5 m x 12.7 mm	51 lbs. With 75 ft. x 3/8" 23 kg	75 ft. 22.5 m	1/3 hp
<b>Sewerooter T-3</b> Pages 14 – 15	Small Drains, Inside Work, On Roofs (Not For Roots)	1-1/4" – 3" and most 4" 30 mm – 100 mm	100 ft. x 1/2" 30 m x 12.7 mm	115 lbs. 52 kg	100 ft. 30 m	1/3 hp Optional 1/2 hp
<b>I-95</b> Pages 24 – 25	Small Drains, Inside Work, On Roofs	1-1/4" – 4" 30 mm – 100 mm (Not For Roots)	Not Applicable	42 lbs. Without Sections 19 kg	125 ft. x 5/8" cable 150 ft. x 7/8" cable 38 m x 15.8 mm 45m x 22.4 mm	1/3 hp Optional 1/2 hp
<b>Root 66</b> Pages 26 – 27	Small Drains, Inside Work, On Roofs	1-1/4" – 4" 30 mm – 100 mm	Not Applicable	42 lbs. Without Sections 19 kg	125 ft. x 5/8" cable 150 ft. x 7/8" cable 38 m x 15.8 mm 45 m x 22.4 mm	1/2 hp
<b>Metro-Rooter</b> Pages 16 – 17	Combination Sewerooter T-3 and Maxi Rooter	2" to 10" 50 mm – 250 mm	50 ft. x 3/4" or 75 ft. x 5/8" or 100 ft. x 1/2" 15 m x 19 mm or 22.5 m x 15.8 mm or 30m x 12.7 mm	153 lbs with 75 ft. 69 kg	150 ft. 45 m	1/3 hp
<b>Speedrooter 92</b> Pages 18 – 19	Combination Sewerooter T-3 and Maxi-Rooter	2" – 10" 50 mm – 250 mm	100 ft. x 3/4" or 5/8" 100 ft. x 1/2" 30 m x 19 mm or 30 m x 12.7 mm	239 lbs. 108 kg	200 ft. 60 m	1/2 hp optional 3/4 hp
<b>Sewermatic 100</b> Pages 20 – 21	Heavy Duty, Roots, Sand, Rags, Industrial Plants	3" – 10" 75 mm – 250 mm	50 ft. x 3/4" or 75 ft. x 5/8" 15 m x 19 mm or 22.5 m x 15.8 mm	160 lbs. With 50 ft. 72 kg	175 ft. 54 m	3/4 hp
<b>Maxi-Rooter</b> Pages 22 – 23	Heavy Duty, Roots, Sand, Rags, Industrial Plants	3" – 10" 75 mm – 250 mm	125 ft. x 3/4" or 150 ft. x 5/8" 37.5 m x 19 mm or 45 m x 15.8 mm	250 lbs. 114 kg	200 ft. 60 m	3/4 hp optional 1 hp
<b>Model 88</b> Pages 28 – 29	Heavy Duty, Roots, Sand, Rags, Industrial Plants	3" – 10" 75 mm – 250 mm	Not Applicable	80 lbs. Without Sections 36 kg	200 ft. 60 m	3/4 hp optional 1 hp
<b>Hot-Rodder</b> Pages 30 – 31	Heavy Duty, Roots, Sand, Rags, Industrial Plants	3" – 10" 75 mm – 250 mm	Not Applicable	96 lbs. Without Sections 13 kg	200 ft. – 60 m 300 ft. – 90 m	3/4 hp optional 1 hp
<b>Rodrunner and Rodrunner "E"</b> Pages 32 – 33	Heavy Duty, Roots, Sand, Rags, Industrial Plants	3" – 10" 75 mm – 250 mm	Not Applicable	90 lbs. Without Sections 41 kg	200 ft. – 60 m 300 ft. – 90 m 500 ft. – 150 m	3/4 hp 1 hp 6.5 hp Gas Engine
<b>Jet-Set</b>	Grease, Sand, Soft Stoppages, and Ice	1/2" hose 4" thru 12" 100 mm x 300 mm 3/8" hose 4" thru 8" 100 mm x 200 mm 1/4" hose 2" thru 4" 50 mm x 100 mm 1/8" hose 1-1/2" thru 2"	400 ft. x 1/2"	1800 lbs. (816 kg)	400 ft. x 1/2" hose	24 hp Gas Engine
<b>J-2512</b>			Not Applicable	295 lbs. (134 kg)	120 m x 12.7 mm	20 hp Gas Engine
<b>J-3080</b>			300 ft. x 3/8"	235 lbs. (107 kg)	300 ft. x 3/8" hose	16 hp Gas Engine
<b>J-3055</b>			300 ft. x 3/8"	203 lbs. (92 kg)	90 m x 9.5 mm	13 hp Gas Engine
<b>J-3000</b>			300 ft. x 3/8"	173 lbs. (78 kg)	200 ft. x 1/4" hose	13 hp Gas Engine
<b>J-2900</b>			150 ft. x 1/4"	130 lbs. (59 kg)	60 m x 6.4 mm	1-1/2 hp 13 amp
<b>J-1600</b>			150 ft. x 1/4"	105 lbs. (48 kg)	75 ft. x 1/8" hose	1-1/2 hp 13 amp
<b>J-1450</b>			Not Applicable	71 lbs. (32 kg)	22.5 m x 3.2 mm	1-1/2 hp 13 amp
<b>J-1400</b> Pages 38 – 41						

Use 1/4" Cable in 1-1/4" – 2" Lines ■ 5/16" Cable in 1-1/2" – 2" Lines ■ 3/8" Cable in 2" – 3" Lines ■ 1/2" Cable in 3" – 4" Lines (Not Roots)  
5/8" Cable in 3" – 6" Lines ■ 3/4" Cable in 4" – 10" Lines ■ 5/8" Sectional in 1-1/4" – 3" Lines ■ 7/8" Sectional in 2" – 4" Lines ■ 1-1/4" Sectional in 3" – 10" Lines