

# Mini-Router™

*Gives You Light Weight with a Long Reach*



**W**ith 75 feet of 3/8" cable and a 1/3 hp motor, the Mini-Router clears lines from roof-top to basement, including kitchen, bath, and laundry drains. You can do heavier work in 4" lines when the Mini-Router is equipped with a 1/2" cable.

This inexpensive, light-weight machine has lots of time-saving features. For instance, you can remove the drum in seconds for more portability or to switch to a different diameter cable – with no mess and no lost time. A distributor tube inside the drum allows you to feed cable in and out without chucking and releasing the cable every few feet – so you finish quicker. An optional power cable feed gives you better feeding and retracting control.

For small drain work, you can order your Mini-Router with a J-Drum or a Dual Drum for handling smaller, more flexible cables. An optional Mini-Router dolly lets you roll the machine to and from the job on 8" semi-pneumatic wheels.



## **Power Cable Feed**

Variable speed power cable feed attachment (optional) gives better feeding and retracting control. Quickly adjusts for 3/8" or 1/2" cables without the need for tools or additional parts. Swings out of the way to make drum changing as easy as ever. Fits all Mini-Router models.

**Catalog Number PO-MR**



## **Flexicore® Cable**

### **Wire Rope Center Construction**

Heavy-gauge wire coiled tightly around 49-strand aircraft-type wire rope and heat treated. Has unequalled strength and the right amount of flexibility. So tough it carries a one-year warranty against defect or breakage.

**Flexicore Patent Nos. 2,244,735 and 2,849,870**

Some Mini-Router safety features: A foot pedal that uses air pressure to start and stop the machine, with no electrical wiring between pedal and motor, a Ground Fault Circuit Interrupter, and a high impact plastic guard covering the motor pulley.



**Mini-Rooter Dolly**

This lightweight but sturdy dolly is designed especially for the Mini-Rooter. It slips on or off in less than a minute and holds the machine securely.

Catalog Number MR-W



**Removable Drum**

You can take the drum off the Mini-Rooter in seconds.



**J-Drum**

With a J-Drum, you're ready for small drain work in seconds. Equipped with a collet chuck with tightening handle. Will hold any Super-Vee cable.

Catalog Number MR-250

**Dual Drum**

Holds two small diameter cables at the same time.

For instance, you can switch from a 1/4" to a 3/8" size without removing either one from the drum. Smaller cable is in an inner drum, while larger cable is between inner

drum and drum shell. Will hold any Super-Vee cable.

Catalog Number MR-280



**Specifications:**

**Weight:**

37 lbs. (17 kg) without cable.

**Dimensions:**

18" deep x 12" wide x 19" high. (45 cm x 30 cm x 46 cm).

**Drum:**

Capacity of 75 ft. of 3/8" or 1/2" Flexicore wire rope center cable. Integral distributor tube.

**J-Drum:**

Capacity of 50 ft. of 1/4" or 5/16" Flexicore cable.

**Dual Drum:**

Capacity of 25 ft. of 1/4" or 5/16" in inner drum. 50 ft. of 5/16" or 3/8" Flexicore cable in outer drum.

**Cutter Set:**

See page 34.

**Motor:**

1/3 hp, with forward-off-reverse switch, spring-loaded mounting for proper belt tension.

**Load Speed:**

165 rpm.

**Belt Guard:**

High impact plastic.

**Power Cable Feed**

(Optional) Drives 1/2" and 3/8" cables.

**Foot Pedal:**

Leaves operator's hands free to control cable. Uses air pressure, so there's no electrical contact between pedal and motor.

**Power Cord:**

10 ft. 3-wire vinyl covered with molded plug. In-line Ground Fault Circuit Interrupter.

**Leather Gloves:**

With double-reinforced palm, for hand protection when guiding cable.

