

Speedrooter 92™

Job Tested Tough



Contractors know that the Speedrooter really can take a beating – from its frame braced at key stress points, to General's exclusive Flexicore® wire rope center cable that's so tough it carries a one-year warranty.

The Speedrooter 92's field tested design offers easy handling. One person can easily load it onto a truck, as the machine slides smoothly from the loading wheel to the handle to the stair climbers and finally to the wheels. The adjustable height handle can be reset to be three inches longer, or more compact, depending upon your preference.

With the driving and pulling power for long, tough jobs, General's Power Cable Feed easily handles 3/4", 5/8", and 1/2" cables. To adjust to different cable sizes, simply turn the knob on top of the feed.

A large drum holds 100 feet of 3/4" or 5/8" Flexicore® cable. For smaller lines, you can switch to a small drum that holds 100 feet of 1/2" cable. Both drums have a see-through inner cage, so you can quickly see how much cable is left in the drum.





Portability, Convenience, and Safety

Equipped with ten-inch wheels, stair climbers, tool box, and Ground Fault Circuit Interrupter.



Stair Climbers and Truck Loaded Wheel

V-Belt and stair climbers let you take the Speedroooter up a flight of stairs yourself. One person can easily load the machine onto the truck.



Small Drum

Holds up to 100 ft. of 1/2" Flexicore cable.



Specifications:

Weight:

115 lbs. (52 kg) without cable.

Dimensions:

26" deep; 22" wide; 41" high, (66 cm x 56 cm x 104 cm).

Interchangeable Drums:

A smaller V-belt is required to drive smaller drum and is standard equipment with PS92-A.

Large Drum:

Equipped with inner drum cage; holds 100 ft. x 3/4" or 5/8" cable.

Small Drum:

Equipped with inner drum; holds 100 ft. of 1/2" cable.

Drum Removal:

Loosen two knobs, remove ringbolt and lift off.

Motor:

1/2 hp with capacitor start, overload protection, and forward-off-reverse switch. 20 ft. power cord and Ground Fault Circuit Interrupter.

Load Speed:

170 rpm.

Wheels:

10" semi-pneumatic heavy-duty with ball bearings. Brake locks wheels during operation.

Foot Switch:

Pneumatic, with no electrical contact between pedal and motor.

Power Cable Feed:

Drives or retracts cable with variable speed at up to 20 ft./min. without having to reverse motor rotation.

Leather Gloves:

With double-reinforced palm, for hand protection when guiding cable.

Cutters:

See Parts and Accessories on page 34.

Cables:

3/4" diameter for 4" to 10" lines and 3" lines without sharp bends; 5/8" diameter for 3" to 6" lines; 1/2" diameter for 3" to 4" lines. (Not for roots.)

Truck Loading Wheel:

Enables one person to lift machine onto bed of truck.

Tool Box:

Attached to rear of machine.

Stair Climbers:

V-belts running on nylon rollers.

