

J-2900 Gas Jet

Big machine features at a bargain price.

J-2900 Specifications:

Pump:

Triplex w/Vibra-pulse®

Pressure:

3000 psi

Flow:

4 gpm

Engine:

11 hp w/Low oil shut off

Hose Reel:

Removable, brass swivel, drag brake, and reel lock, 300 ft. x 3/8" capacity

Weight:

173 lbs. (78 kg)

Dimensions:

25-1/2" L x 28-1/2" W x 42" H
(65 cm x 72 cm x 107 cm)



J-2000 Gas Jet

Gas jet power in a compact package.

J-2000 Specifications:

Pump:

Triplex w/Vibra-pulse®

Pressure:

2200 psi

Flow:

3 gpm

Engine:

5.5 hp w/Low oil shut off

Hose Reel:

Removable, brass swivel, drag brake, and reel lock, 200 ft. x 3/8" capacity

Weight:

115 lbs. (52 kg)

Dimensions:

30" L x 26" W x 35" H
(76 cm x 66 cm x 89 cm)



The J-2900 is an economical alternative to the J-3000. It's lighter and more maneuverable, yet maintains the same pressure and flow rate as the J-3000. It's driven by an 11 hp Honda engine connected directly to a 3000 psi, 4 gallon per minute triplex pump with Vibra-pulse® on demand. A removable 300 ft. capacity hose reel with drag brake, reel lock and brass swivel is mounted on a heavy duty frame with four pneumatic tires. Safety features include a thermal relief valve, along with a back flow check valve and inlet filter. An optional spray wand is available.

The lightweight J-2000 delivers more pressure and flow than you can get in an electric jet. Its operating weight is just 135 lbs., yet it delivers 2200 psi at three gallons per minute. A triplex pump and 5.5 hp Honda engine gives you reliability, while Vibra-pulse® on demand makes it easier to get the hose around bends. You can transport and maneuver the J-2000 easily on its two pneumatic tires. Includes removable 200 ft. capacity hose reel with adjustable drag brake and brass swivel, glycerine gauge, tool box, thermal relief valve, inlet filter, and back flow check valve. The safety foot pedal and spray wand are optional.