

J-3080 Gas Jet

Get high water flow without a trailer.

The J-3080 gives you the increased cleaning power of 8 gallons of flow per minute without risking pump damage if your water supply can't match the pump demand. A 12 gallon buffer tank mounted on the frame gives you the safety margin you need when using a high flow water jet to clear larger and more difficult lines. The tank extends the operating time as well. A low water shut off valve protects the pump until the tank is refilled. A 20 hp Honda engine with electric start drives a 3000 psi, 8 gpm pump through a 2 to 1 gear reducer. The pump features Vibra-pulse® on demand, to help propel the hose on long runs and around tight bends.

Standard safety features include a thermal relief valve to protect the pump from heat damage, along with a back flow check valve and inlet filter. The unit is mounted on a heavy duty frame with four 13" pneumatic tires. A wheel brake keeps the machine solidly positioned on the job. Complete with tool box, chemical injector, and spray wand with trigger.

J-3080 Specifications:

Pump:

Triplex w/Vibra-pulse®

Pressure:

3000 psi

Flow:

8 gpm

Engine:

20 hp Honda
w/Low oil shut off,
electric start, and
gear reducer

Tank Capacity:

12 gallons
w/Low water shut off

Weight:

295 lbs. (134 kg)

Dimensions:

37" L x 30-1/2" W x 42-1/2" H
(94 cm x 77.5 cm x 108 cm)



CR-300 Cart-Reel™

The optional Cart-Reel™ is a must for professionals. It lets you use the power of a gas jet in buildings and confined spaces where exhaust fumes could be hazardous, while the gas jet stays outside.

The Cart-Reel comes with pneumatic tires, a 300 ft. capacity hose reel, reel brake, gauge, and a shut-off valve.

